




## 20-30 Watt Universal 3-Wire Input Adapter PSC30U Adapter Series Meets CEC and EISA Requirements



### Features

- Low Cost
- EISA Energy Efficiency Compliance
- Class B EMI
- Non-Vented/Spill-proof Case
- Low Profile Design

### Applications

- Portable Equipment
- Peripherals
- Networking
- Gaming Machines

### Safety Approvals

- cUL/UL
- Meeting Cal. Prop. 65
- C-Tick
- SAA

### Mechanical Characteristics

- Length: 98.5mm (3.88in)
- Width: 55mm (2.17in)
- Height: 31.5mm (1.24in)
- Weight: 243g (8.57oz.)

### Output Specifications

Model	DC Output Voltage	Load		Efficiency Level <sup>(1)</sup>
		Min.	Max.	
PSC30U-050	+5V	0A	4.0A	IV
PSC30U-120	+12V	0A	2.5A	IV
PSC30U-240	+24V	0A	1.25A	IV
PSC30U-480	+48V	0A	0.625A	IV

(1) Level IV efficient products do not qualify for CE marking and therefore cannot be sold to countries in the EU

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications and contact information.

**Input:**

**AC Input Voltage Rating**  
100 to 240V AC

**AC Input Voltage Range**  
90 to 264V AC

**AC Input Frequency**  
47 to 63Hz

**Input Current**  
0.8A (RMS) maximum at 115V AC  
0.5A (RMS) maximum at 240V AC

**Leakage Current**  
3.5mA maximum

**Inrush Current**  
60A for 240V AC at maximum load  
(Cold start at ambient 25°C)

**Input Power Saving**  
0.5W maximum at no load at 115V AC

**Output:**

**Power**  
20W for 5V  
30W for 12V, 24V, 48V

**Ripple**

5V	50mV
12V	120mV
24V	240mV
48V	480mV

(Measured after 10 minutes warm up at 25°C with 12-inch twisted pair terminated with a 10uF capacitor and 0.1uF ceramic in parallel.)

**Regulation Line & Load**  
±5%

**Efficiency**  
Level IV Compliant  
For level V compliance see model PSC30U-V

**Environmental:**

**Temperature**

Operation	0 to +40°C
Non-operation	-30 to +85°C
Relative Humidity	20 to 90%

**Emissions**  
FCC Class B  
EN55022 Class B

**Immunity**  
IEC61000-4-2  
IEC61000-4-3  
IEC61000-4-4  
IEC61000-4-5  
IEC61000-4-6  
IEC61000-4-8  
IEC61000-4-11  
EN61000-3-2

**Hold-up Time**  
16mS minimum at 120V AC and maximum load

**Over-Voltage Protection**  
By Zener Clamping, Adapter will be shut down

**Over-Current Protection**  
Output equipped with short circuit protection - auto restart

**Short-Circuit Protection**  
Output can be shorted without damage

**Insulation**  
Input to Output: DC 500V 7M ohm

**Dielectric Withstand (Hi-pot) Test**  
Input to Output: 1500V AC for 1 min., 10mA

**MTBF**  
50K hours minimum at full load and 25°C

**DC Output Connector**  
2.1 x 5.5 x 10mm Center Positive Standard

**DC Cord Length**  
12V, 24V & 48V Models – 1850mm (72.8in)  
5V model – 1500mm (59.1in)

**Dimension Diagram Unit: mm**

