

SUNON KDE Series

DC Brushless Fan

8025

:80x80x25mm



Model	P/N	Bearing	Rating Voltage (VDC)	Power Current (AMP)	Power Consumption (WATTS)	Speed (RPM)	Air Flow (CFM)	Static Pressure (Inch-H ₂ O)	Noise (dBA)	Weight (g)
KDE2408PTS1-6		⊙	24	0.12	2.9	3000	41.7	0.18	34	100
KDE2408PTS2-6		⊙	24	0.10	2.4	2650	34.4	0.16	30	100
KDE2408PTS3-6		⊙	24	0.07	1.7	2200	29.4	0.11	24.5	100
KDE2408PTB1-6		○	24	0.12	2.9	3200	42.5	0.23	36.5	100
KDE2408PTB2-6		○	24	0.10	2.4	2800	35	0.20	32.5	100
KDE2408PTB3-6		○	24	0.07	1.7	2500	30	0.14	28.5	100

9225

:92x92x25mm



Model	P/N	Bearing	(VDC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
KDE2409PTS1-6		⊙	24	0.12	2.9	2800	50	0.17	35	121
KDE2409PTS2-6		⊙	24	0.09	2.2	2500	44	0.15	33	121
KDE2409PTS3-6		⊙	24	0.07	1.7	2100	39	0.11	27	121
KDE2409PTB1-6		○	24	0.12	2.9	3000	51	0.20	37	121
KDE2409PTB2-6		○	24	0.09	2.2	2600	45	0.18	34	121
KDE2409PTB3-6		○	24	0.11	2.7	2300	40	0.13	28	123

12025

:120x120x25mm



Model	P/N	Bearing	(VDC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
KDE1212PTS1-6A		⊙	12	0.38	4.6	3000	88	0.27	44	200
KDE1212PTS2-6A		⊙	12	0.30	3.6	2700	78	0.21	40	200
KDE1212PTS3-6A		⊙	12	0.20	2.4	2300	67	0.16	35	200
KDE1212PTB1-6A		○	12	0.38	4.6	3100	90	0.28	44.5	200
KDE1212PTB2-6A		○	12	0.30	3.6	2800	80	0.22	41	200
KDE1212PTB3-6A		○	12	0.20	2.4	2400	69	0.17	35.5	200
KDE2412PTS1-6A		⊙	24	0.22	5.3	3000	88	0.27	44	200
KDE2412PTS2-6A		⊙	24	0.17	4.1	2700	78	0.21	40	200
KDE2412PTS3-6A		⊙	24	0.13	3.1	2300	67	0.16	35	200
KDE2412PTB1-6A		○	24	0.22	5.3	3100	90	0.28	44.5	200
KDE2412PTB2-6A		○	24	0.17	4.1	2800	80	0.22	41	200
KDE2412PTB3-6A		○	24	0.13	3.1	2400	69	0.17	35.5	200

12038

:120x120x38mm



Model	P/N	Bearing	(VDC)	(AMP)	(WATTS)	(RPM)	(CFM)	(Inch-H ₂ O)	(dBA)	(g)
KDE1212PMSX-6A		⊙	12	0.63	7.6	3100	119	0.32	45	326
KDE1212PMS1-6A		⊙	12	0.57	6.8	3000	107	0.30	41	326
KDE1212PMS2-6A		⊙	12	0.43	5.1	2700	97	0.24	36	326
KDE1212PMS3-6A		⊙	12	0.27	3.2	2300	83	0.18	34	326
KDE1212PMBX-6A		○	12	0.63	7.6	3150	120	0.34	46.5	326
KDE1212PMB1-6A		○	12	0.57	6.8	3100	108	0.31	42	326
KDE1212PMB2-6A		○	12	0.43	5.1	2800	98	0.25	36.5	326
KDE1212PMB3-6A		○	12	0.27	3.2	2400	84	0.19	35	326
KDE2412PMSX-6A		⊙	24	0.30	7.2	3100	119	0.32	45	326
KDE2412PMS1-6A		⊙	24	0.28	6.7	3000	107	0.30	41	326
KDE2412PMS2-6A		⊙	24	0.23	5.5	2700	97	0.24	36	326
KDE2412PMS3-6A		⊙	24	0.17	4.0	2300	83	0.18	34	326
KDE2412PMBX-6A		○	24	0.30	7.2	3150	120	0.34	46.5	326
KDE2412PMB1-6A		○	24	0.28	6.7	3100	108	0.31	42	326
KDE2412PMB2-6A		○	24	0.23	5.5	2800	98	0.25	36.5	326
KDE2412PMB3-6A		○	24	0.17	4.0	2400	84	0.19	35	326

12

*Specifications subject to change without notice