

BLOWER DC FANS

BN SERIES Ø175x69 mm 48v

- * Material: Impeller (UL 94V-0) & Frame: Diecast Aluminum
- * Lead Wires: UL 1007 AWG #22 or Equivalent
- * Impeller: 7 Blades
- * Rotational direction CW view from front face
- * Weight: 830g (29.28 OZ)



ASIA VITAL COMPONENTS CO., LTD. Six Sigma

MODEL		Bearing Type	Rated Voltage	Operating Voltage Range	Rated Current	Rated Input Power	Speed	Maximum Air Flow	Maximum Air Pressure	Acoustic Noise	Life expectancy L ₁₀ @40°C		
PART NO.	SIGNAL	B.T.S.R	VDC	VDC	Amp	Watt	R.P.M.	m ³ /min	CFM	mmH ₂ O	IN H ₂ O	dB-A	hours
BN17569_48L	-FG/RD	B	48	32 to 80	0.50	24.0	2700	7.892	278.72	29.8	1.173	62.5	70000
* BN17569_48M	-FG/RD	B	48	32 to 80	0.75	36.0	3100	9.086	320.86	40.0	1.575	66.0	70000
BN17569_48H	-FG/RD	B	48	28 to 60	1.15	55.2	3600	10.575	373.44	54.1	2.130	69.5	70000
BN17569_48U	-FG/RD	B	48	28 to 53	1.55	74.4	4000	11.68	412.46	67.4	2.654	72.5	70000

www.cwc-group.com

