

DC Fan Motors

SAN ACE □ **60mm**
PICO ACE



DC Fan Motors

Silent (R type), high rotating speed

General specifications

Motor protection system ···· Current cut system (with reverse-connection protection)

Dielectric strength ······ 50/60 Hz, 500 VAC, 1 minute
(between lead conductor and frame)

Operating thermally range -10°C to +60°C (non-condensing)

Fan power lead ······ J, G, D, S, H, F, W speeds, ⊕ red, ⊖ black
M speed, ⊕ red, ⊖ blue

15mm thick
Specifications

Model No	Rated voltage (V)	Operating voltage range (V)	Rated current (A)	Rated input (W)	Rated rotating speed (min ⁻¹)	Air flow (m ³ /min) (CFM)	Static pressure (Pa)	Noise (dB(A))	Mass (g)
109P0605H702	5	4.5~5.5	0.26	1.30	4,100	0.40 / 14.1	38.2	32	60
109P0605M702			0.15	0.75	3,100	0.30 / 10.6	22.6	25	
109P0612S702			0.15	1.80	5,000	0.48 / 17.0	58.8	36	
109P0612H702	12	7~13.8	0.09	1.08	4,100	0.40 / 14.1	38.2	32	
109P0612M702			0.07	0.84	3,100	0.3 / 10.6	22.6	25	
109P0624H702	24	14~27.6	0.06	1.44	4,100	0.4 / 14.1	38.2	32	
109P0624M702			0.04	0.96	3,100	0.3 / 10.6	22.6	25	

Typical air flow and static pressure characteristics

